

LED COPPER HAT

Design Pro LED in a definitive yet unassuming copper housing.
Will develop a natural verdigris over time.

15850 CO - Unfinished Copper

Copper (copper will naturally patina over time)

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity,
and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA
Multiply fixture VA by the number of fixtures used
to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm
3000K = 35 Lm/W

30" of useable #18-2, SPT-1W leads. Cable connector supplied

8" In-ground stake

15601 - Surface Mounting Flange
15607 - Surface Mounting Bracket

15350 - on page 83

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing
Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'

Footcandles 8.77 6.57 4.37 2.77 1.77 1.57 0.61 0.41 0.28



WT850

**Guaranteed not
to burn out for
15 years (10
commercially)**

POWERED BY
DESIGN PRO LED
TECHNOLOGY

WITH
Radiax™
OPTICS

LandLight
Enhance The Night

**Professional-grade LED lighting and
system components, designed and
engineered for optimum all-weather
performance with natural lighting
effects, deliver professional results.**

Enhance The Night - www.landlight.ca